GENERAL SHELTERS SPECIFICATION SHEET

| | | _ | | |
|-----------------------|--|---------------------|-------------|-----------------------------------|
| Building Size | 18x56 | <u>Doors:</u> | <u>qty.</u> | |
| Roof Style | Gable w/ 9" OH and Chaparral Front | Exterior Door: | 2 | 36"x80" Fiberglass Out Swing |
| Porch | N/A | Exterior Door: | | |
| Floor: | | | | Door Insert: |
| | Double Skids | | | Door Insert: |
| | | | and to | |
| | R-19 Fiberglass w/ Vapor Barrier | • 5 | <u>qty.</u> | Door Color: |
| | 2" x 8" on 16" Center | Interior Doors | 1 | 22" A/C Flat Panel Stain Grade |
| Decking: | 3/4" Subfloor | | 1 | 24" Pocket Flat Panel Stain Grade |
| Floor Covering: | | | 2 | 30" Dbl. Louver Panel Stain Grade |
| Tile: | Pick a tile | | 2 | 30" Pocket Flat Panel Stain Grade |
| 26oz. Carpet: | | | 3 | 32" Flat Panel Stain Grade |
| • | | | | |
| Exterior: | | | | |
| | 8' Walls | Windows: | | |
| | 2" x 4" x 91.5" on 16" Center | | arts. | Vinyl |
| | | Window Type: | | |
| Bottom Plate: | | | 2 | 18"x36" Low E Insulated |
| | Double 2" x 4" | | | 36"x 24" Low E Insulated Fixed |
| | 7/16" OSB w/ House Wrap | | 1 | 36"x 36" Low E Insulated |
| | R-15 Fiberglass | | 5 | 36"x 66" Low E Insulated |
| Siding: | 29 ga. | | | |
| Window Trim: | 29 ga. | Window | Color: | |
| | | 4" Band Co | olor | |
| nterior: | | | | |
| | 2" x 4" x 91.5" on 16" Center | Electrical: | atv | |
| | | Electrical: | <u>qty.</u> | |
| | Paneling: | • | | 000 4 5 1 1 5 1 |
| Cabinets: | | Load Center: | 1 | |
| | All Cedar | Receptacles: | | 15 amp.CGFI Receptacle Color |
| Counter Top: | | GFI Receptacles: | 6 | Interior GFI |
| Closets: | 2 rod and Cedar Shelf | Outside Receptacles | 2 | Exterior GFI |
| Pantry: | 1 | Lighting: | 3 | Ceiling Fan |
| Misc.: | | Lighting: | | LED Disk |
| Mirror: | | Lighting: | | |
| | E PARO Batilloom | Porch Light | | Galvanized |
| Roof: | Engineered on 04" Contor | | | |
| | Engineered on 24" Center | Misc.: | | Smoke Detector |
| Celling: | 29ga. Galvalume | Exhaust Fans: | 2 | 110 CFM Exhaust Fan |
| | R-30 Fiberglass (Gables Only) | | | |
| Decking: | Radiant 7/16" OSB w/ Felt Paper | <u>Plumbi</u> | ing: | |
| Roofing: | 26ga | Bathroom #1: | 1 | 60" Shower w/seat Kit |
| Rake Trim: | 26ga. | Bathroom #2: | 1 | 60" Tub /Shower Kit |
| Anchor Straps: | per side Skid Attached - Field Installed | Water Closets: | Elonga | ted |
| | • | Lavatory: | Porcel | ain Sink |
| HVAC: | | Water Heater: | | |
| | 2.5 Ton Residential Unit | | | ential Brass Body |
| A/O - Heating. | 2.0 Tott Hoolderhildt Offic | | | ess Undermount Double Bowl |
| | | Silik. | Stairile | ess officermount bouble bowl |
| | | | | |
| | | | | ances: |
| SPECIAL ITEMS: | Cedar Self over Washer and Dryer | | | frigerator (36") 1 Stainless |
| | 3 windows in the raised roof section | 30 | " Slide | e in Range 1 Stainless |
| | | | Dishv | vasher 1 Stainless |
| | | | Dı | ryer 1 White |
| | | Micro | owave | w/ ventless 1 Stainless |
| | | | Wa | sher 1 White |
| | | | | 0 |
| | | | | U |
| | | | | |
| Model: | Chaparral II sq.ft. | Approval By: | | |
| | | | | |
| Dealer: | | Date: | | |
| | | | | |

1/27/2025